



PLAFOND
PLAST SRL

listino prezzi *price list*

01/2022

pressione, fognatura, edilizia
pressure, sewage, building

all around the world



PVC - NORMA
UNI EN 1329-1



TUBI IN PVC RIGIDO BICCHIERE AD INCOLLAGGIO COLORE ARANCIO - SERIE SPECIAL EDIL

Ø esterno mm		32	40	50	63	80	100	125	140	160	200
spessore mm						2,0	2,1	2,2	2,2	2,3	2,9
barra da 3 mt	€	—	—	—	—	8,95	11,25	14,14	16,65	20,87	32,86
barra da 2 mt	€	—	—	—	—	6,36	7,99	10,06	11,84	14,50	22,79
barra da 1 mt	€	—	—	—	—	3,34	4,18	5,29	6,18	7,59	11,91

TUBI IN PVC RIGIDO BICCHIERE AD INCOLLAGGIO COLORE ARANCIO - SERIE SPECIAL EXTRA

Ø esterno mm		32	40	50	63	80	100	125	140	160	200
spessore mm		2,7	2,7	2,7	2,7	2,7	2,7	2,7	2,7	2,8	3,5
barra da 3 mt	€	4,32	5,52	7,02	8,61	11,09	13,14	16,58	19,48	23,85	37,51
barra da 2 mt	€	3,08	3,94	5,01	6,54	8,43	9,38	11,83	13,89	17,02	26,76
barra da 1 mt	€	1,62	2,07	2,63	3,40	4,37	4,91	6,20	7,27	8,91	14,01


TUBI IN PVC RIGIDO BICCHIERE AD INCOLLAGGIO COLORE ARANCIO - SERIE 302 UNI EN 1329 TIPO B

Ø esterno mm		32	40	50	63	80	100	125	140	160	200
spessore mm		3,0	3,0	3,0	3,0	3,0	3,0	3,2	3,2	3,2	3,9
barra da 3 mt	€	5,86	7,48	9,50	12,13	14,27	17,00	22,76	25,57	29,30	44,67
barra da 2 mt	€	4,49	6,01	7,63	9,78	11,26	12,56	17,52	20,70	22,94	34,86
barra da 1 mt	€	2,58	3,48	4,42	5,67	6,57	7,35	10,30	12,23	13,62	20,78
quantità tubi per bancale		864	750	520	320	200	130	80	63	48	30

Tubazioni in PVC rigido per lo scarico delle acque calde delle apparecchiature elettrodomestiche

Temperatura massima dei fluidi convogliati 70°C. Per scarichi discontinui con le normali portate delle apparecchiature elettrodomestiche: temperatura massima di 95°C per una durata non maggiore di 1 minuto. I diametri devono essere dimensionati in modo che venga rispettato il tempo massimo di scarico ammesso.

RACCORDI PER TUBI IN PVC RIGIDO ARANCIO - UNI EN 1329




CURVA 45°

Ø mm	32	40	50	63	80	100	125	140	160	200
€	0,63	0,51	0,79	0,99	1,39	1,78	2,85	3,70	5,10	8,72




CURVA 87° 30'

Ø mm	32	40	50	63	80	100	125	140	160	200
€	0,74	0,60	0,90	1,27	1,53	2,50	3,29	4,60	7,10	11,60



BRAGA 45° - 87° 30'

Ø mm	32	40	50	63	80	100	125	140	160	200
€	1,00	1,10	1,30	1,87	2,95	3,85	6,77	7,65	12,06	22,35




BRAGA RIDOTTA 45° - 87° 30'

Ø mm	32	40	50	63	80	100	125	140	160	200
€	-	-	-	-	-	9,15	11,20	14,40	19,10	32,70



ISPEZIONE LINEARE

Ø mm	32	40	50	63	80	100	125	140	160	200
€	-	-	-	-	18,70	11,20	14,00	15,24	21,34	33,30



SIFONE FIRENZE

Ø mm	32	40	50	63	80	100	125	140	160	200
€	-	-	-	-	15,65	16,26	21,95	30,70	39,60	66,70



TAPPO A VITE

Ø mm	32	40	50	63	80	100	125	140	160	200
€	-	-	-	1,70	2,40	2,83	3,48	7,39	8,50	9,80



GIUNTO DI RIPARAZIONE

Ø mm	32	40	50	63	80	100	125	140	160	200
€	-	-	-	-	10,00	6,90	12,15	14,00	15,50	24,00



	Ø	40 / 32	50 / 40	63 / 40 50	80 / 50 63	100 / 63 80	125 / 50 63 80 100	140 / 100 125
AMPLIATORE (bicchiere sul Ø minore)	€	0,34	0,54	0,80	1,30	2,30	2,50	3,00
RIDUTTORE (bicchiere sul Ø maggiore)								



	Ø	160 / 125 140	200 / 125 140 160					
AMPLIATORE (bicchiere sul Ø minore)	€	4,20	7,51					
RIDUTTORE (bicchiere sul Ø maggiore)								



PLAFOND
PLAST SRL

43010 Roccabianca
Parma - Italy
Strada Padana, 6
Tel. +39 0521 876430-876035
fax +39 0521 876110
info@plafondplast.com
www.plafondplast.com

